

Copyright by 600/1878542.3



Equiplite[™]

Non Swivelling (NS) | Quick Connectors



Soft connector to replace stainless steel...

Equiplite™ Soft Connector use high tensile alloy and DSK 75 ULTRA loops to take the connection load. This allows the NS Connector to be extremely light (at least 80% to 90% less than traditional stainless fittings assemblies of the same load).

Correct fair lead | compact | less windage, quick and easy to operate compared to traditional stainless fittings.

NS Connectors are used on cruising and top competitive boats for :

- | | |
|-------------------------------|---------------------------|
| Genoa sheets | Stay sails sheets |
| Genakker sheets Guys | Outhall system |
| Runner 2:1 on deck | Mast top connector |

And their flexibility makes them particularly good for the most difficult use for:

Main Halyard 1:1

The advance of the quick loop.

With the specially designed NS Connector we created a system that becomes an extension of the spliced rope. And is easy and quick to attach and detach, even with cold & wet hands. Three times stronger than a bowline, never hard to undo and less windage

High-strength material— impact resistant.

The NS Connector has a high tensile aluminium body technology. With unmatched impact and wear resistance. The NS Connector does not have a self tightening or jamming action as “dog bone”. It is more compact, lighter and easier to operate compared to “dog bone” types or bow lines.

Reduced damage to the yacht, safe

Our compact loop connector with velcro wrap reduces damage to the forestays and rigging . Safer: light weight reduces risk of injury when flogging, reduced damage to masts, spinnaker tracks, topsides etc. Will not jam even if overloaded, will operate close to break load. And will not fatigue and fail prematurely compared to stainless. Loops are replaceable.



On request full cover

Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs.

Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

All prices are retail prices in Euro.

All data approx and subject to change without notice.

Other sizes available on special order.

Unspecified dims. mm.
Break load approx. 2 x SWL.

Use max line size for optimal connection

Part	Max. line (mm.)	Throat (mm.)	SWL (Kg.)	Wt.(Gm.)
35-20NS	35	200	40.000	650
34-18NS	34	200	35.000	380
34-16NS	34	180	28.000	350
32-16NS	32	180	28.000	350
30-16NS	30	180	28.000	350
34-14NS	34	150	18.000	320
32-14NS	32	150	18.000	320
30-14NS	30	150	18.000	300
30-12NS	30	150	14.000	290
28-12NS	28	120	13.000	285
26-12NS	26	120	13.000	280
24-12NS	24	120	13.000	280
All connectors above are custom build				
20-12NS	20	110	13.000	160
18-10NS	18	100	9.500	115
16-10NS	16	80	9.500	113
14-8 NS	14	70	6.500	72
14-7 NS	14	70	6.000	50
12-6 NS	12	30	4.900	34
10-6 NS	10	30	4.900	32
10-5 NS	10	25	3.000	19
8-5 NS	8	25	3.000	18
8-4 NS	8	20	2.200	8
6-4 NS	6	20	2.200	8
5-3 NS	5	20	1.200	6