

Copyright by 600/1878542.3



Equiplite[™]



Equiplite™ Spinnaker Blocks SpB

Equiplite™ Spinnaker blocks are similar in design to Equiplite™ snatch blocks but employ fixed sides with quick attach loops. They employ wide acetyl or alloy sheaves to pass two sheets for peeling under load. For compactness and less windage. This allow the blocks to be extremely light (at least 75% less than competitive assemblies of the same load).



High-strength material— low friction, impact resistant

The spinnaker blocks use moulded carbon composite side plates, with high-tensile Hardkote-anodized aluminium sheaves for high load types. The bearing has an advanced high load low friction polymer bearing technology, giving unparalleled loaded friction efficiency of at least 92% for HL. (With dry operation, without need for lubrication). These spinnaker blocks have unmatched impact and wear resistance, together with their light weight.

Reduces possible damage to the yacht, safe

With our compact loop system and clean protection reduces damage to the yacht.
Safer: Extremely light weight reduces risk of injury when flogging.

Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs.

Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

All prices are retail prices in Euro.

All data approx and subject to change without notice.

Other sizes available on special order.

**Unspecified dims. mm.
Break load approx. 2 x SWL.**

SpB: Spinnaker block

Part	Sheave ϕ	2 X Max Sheets (mm.)	Throat (mm.)	SWL (Kg.)	Wt.(Gm.)
64-80-12 HL SpB	80	2 X 22	87	14.000	950
64-80-12 LL SpB	80	2 X 22	87	8.000	950
54-74-10 HL SpB	74	2 X 18	80	9.000	600
54-74-10 LL SpB	74	2 X 18	80	5.500	550
46-65-8 HL SpB	65	2 X 16	60	6.000	410
46-65-8 LL SpB	65	2 X 16	60	4.000	410
36-55-6 HL SpB	55	2 X 14	45	4.000	290
36-55-6 LL SpB	55	2 X 14	45	3.000	290
30-46-5 HL SpB	46	2 X 14	37	3.000	175
30-46-5 LL SpB	46	2 X 14	37	2.200	175
25-43-5 HL SpB	43	2 X 12	36	3.000	170
25-43-5 LL SpB	43	2 X 12	36	2.200	170
20-42-4 HL SpB	42	2 X 10	32	2.200	85
20-42-4 LL SpB	42	2 X 10	32	1.500	85

Above HL = High load version employing high load low friction polymer