





# Equiplite™

## Furling Systems | CODE 0

- | Stay sails
- | Structural furlers



### High-strength material— low friction, impact resistant

The sheave and top swivels are high-strength alloys with Carbon fibre drums. And have unmatched performance.

### Stands up to salt, sun and long-term wear

The carbon body is UV protected. DSK 75 ULTRA is full UV resisting and has an extra cover protection for chafe coated with a special developed UV coating.

### Low-friction

The combination of our high quality roller bearing and DSK 75 ULTRA loops that take the loads directly through the centre of the bearing, give the most efficient, lightest and long-lasting furler.



Stay in the lead with Equiplite™ `s strong ultra Lightweight Carbon Loop Furling Drum System

Equiplite™ Furling Systems using DSK 75 ULTRA loops to take the loads directly through the centre of the bearing. The advance is less friction, combined with the sealed bearings. Tack as low as possible on deck. They typically weigh at least 60 % less than competitive assemblies of the same load.

### Lightest furler lock system

After furling the code 0 | stay sail with 4/5 turns with the sheet around the sail, you can lock the furler. This way you can clean up the sail and set up the sail without it unfurling.

Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs.

Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

**Drum: The assemblies below have: Fixed line with | Quick connect and disconnect soft loop**

Part	SWL (Kg.)	Wt (Gm.)	Dia (mm.)	Length (mm.)	Line (mm.)
2 FS	1.4 t.	235	90	120	6
3 FS	2 t.	395	100	120	6
4 FS	3 t.	410	123	135	8

**The assemblies below have the added features of: Quick fit and removable line | Roller entry and exits | And sheave is lockable | Quick connect and disconnect soft loops and bottom connections.**

Part	SWL (Kg.)	Wt (Gm.)	Dia (mm.)	Length (mm.)	Line (mm.)
4 FS	3 t.	473	123	135	8
5 FS	4 t.	810	156	155	8
6 FS	6 t.	820	156	170	8
8 FS	7,6 t.	1.250	190	205	8
10 FS	11 t.	1.750	223	250	10
12 FS	16 t.	2.400	265	300	12
14 FS	20 t.	2.990	300	330	14
18 FS	30 t.	4.300	375	480	18
22 FS	45 t.	5.800	450	580	22

**Drum & Swivel set**

Part	SWL (Kg.)	Wt 1:1 (Gm.)	Wt. 2:1 (Gm.)	
2 FS	1.400	365	412	
3 FS	2.000	555	599	
4 FS	3.000	658	706	
5 FS	4.000	1.010	1.105	
6 FS	6.000	1.110	1.268	
8 FS	7.600	1.700	2.090	
10 FS	11.000	2.550	3.168	
12 FS	16.000	3.600	4.800	
14 FS	20.000	4.590	6.190	
18 FS	30.000	6.600	8.900	
22 FS	45.000	8.900	12.000	